



GasAlertClip EXTREME

single gas detector

Up to three years of continuous maintenance-free protection


As the world's most popular and widely used zero-maintenance gas detector, the GasAlertClip Extreme offers continuous, reliable protection. Available in two year or three year versions, this single gas detector requires no calibration, sensor replacement, battery replacement, or battery charging. Compatible with the MicroDock II automatic test system, the simplicity of the GasAlertClip Extreme combined with minimal training requirements and negligible maintenance costs, make the GasAlertClip Extreme one of the most cost-effective PPE solutions for facility workers and on-site contractors.

H₂S

CO

O₂

SO₂



Don Wolf & Associates, Inc

21955 Plummer Street
Chatsworth, CA 91311
Toll Free: (800) 266-2046
Phone: (818) 885-5800
Fax: (818) 885-5855
Website: www.donwolf.com
Email: sales@donwolf.com

**WATER
RESISTANT** 

Easy gas identification with color coded labels and LCD indication:





- Durable, reliable and easy to use with no downtime
- Record keeping is accurate and easy with automatic event logging
- Exceptionally low cost of ownership

BWF
Technologies
by Honeywell

Wear yellow. Work safe.

Standard features of BW products:

- Compact and lightweight design makes it comfortable to wear
- Water-resistant
- Compatible with BW MicroDock II automatic test station
- Full function self-test of sensor, battery status, circuit integrity and audible/visual alarms
- Bright wide-angled visual alarm bars
- Built-in concussion-proof boot

GasAlertClip Extreme Specifications	
Size	1.1 x 2.0 x 3.2 in. / 2.8 x 5.0 x 8.1 cm
Weight	2.7 oz. / 76 g
Temperature	H ₂ S: -40 to +122°F / -40 to +50°C CO: -22 to +122°F / -30 to +50°C SO ₂ : -22 to +122°F / -30 to +50°C O ₂ : -4 to +122°F / -20 to +50°C
Humidity	5% - 95% RH (non-condensing)
Alarms	- Visual, vibrating, audible (95dB) - Low, High
Tests	Full function self-test on activation and every 20 hours, and automatic battery test every 2 hours
Typical battery life	Two years (H ₂ S, CO, SO ₂ or O ₂) or three years (H ₂ S or CO)
Ratings	EMI/RFI: Complies with EMC Directive 89/336/EEC IP 66/67
Certifications and approvals	 Class I, Div. 1, Gr. A, B, C, D  American Bureau of Shipping ATEX: CE II 1 G T4 Ex ia IIC T4 IECEX: Ex ia IIC T4 CE: European Conformity
Warranty	2 or 3 years from activation (given normal operation), plus 1 year shelf life

Additional GasAlertClip Extreme features:

- Large confidence LCD displays life remaining in months, days and hours
- Displays peak alarm exposures encountered on demand
- User-activated daily self-test
- Internal vibrating alarm for high noise environments
- Records and transmits gas alarm events

Options and Accessories



MicroDock II compatible



Concussion-proof boot



Bulk package of 50 units



IR DataLink

For a complete list of accessories, please contact BW Technologies.

Sensor Specifications

Gas	Measuring Range	Low Alarm Level ¹	High Alarm Level ¹
2 or 3 year detector			
H₂S	0 - 100 ppm	10 ppm	15 ppm
CO	0 - 300 ppm	35 ppm (30 ppm UK/EU)	200 ppm
2 year detector only			
SO₂	0 - 100 ppm	5 ppm	10 ppm
O₂	0 - 30.0 % by vol.	19.5 %	23.5 %

¹ Alarm set points are not user adjustable. If different set points are required please indicate at time of order.
 Note: H₂S, CO and SO₂ sensors do not require calibration; the O₂ sensor is self-calibrating

Locally available from

Don Wolf & Associates, Inc

21955 Plummer Street
Chatsworth, CA 91311

Toll Free: (800) 266-2046

Phone: (818) 885-5800

Fax: (818) 885-5855

Website: www.donwolf.com

Email: sales@donwolf.com



Corporate Headquarters

2840 - 2 Avenue S.E.
Calgary, AB, Canada T2A 7X9
Phone: +1-403-248-9226

www.gasmonitors.com

USA 1.888.749.8878
Canada 1.800.663.4164
Australia +61.3.9464.2770

info@gasmonitors.com

Europe +44 (0)1295 700 300
France +33 (0) 442 98 17 70
Middle East +971-4-8871766

China +86 10 6786 7305
S.E. Asia +65 6580 3468
Other Countries +1-403-248-9226

DUE TO ONGOING RESEARCH AND PRODUCT IMPROVEMENT, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.



GasAlert EXTREME

single gas detector



Long-term solution

Designed with durability and comfort in mind, the GasAlert Extreme reliably monitors for any single gas hazard within its wide range of available toxic gas models. With easy on/off operation, this single gas detector offers extended longevity with a two year field-replaceable battery and sensor. Calibration is a simple automatic procedure and is compatible with BW's MicroDock II automatic test and calibration system. A wide range of user options, multi-language display and datalogging functionality make the GasAlert Extreme an ideal solution for many applications.



Don Wolf & Associates, Inc

21955 Plummer Street
Chatsworth, CA 91311
Toll Free: (800) 266-2046
Phone: (818) 885-5800
Fax: (818) 885-5855

Website: www.donwolf.com
Email: sales@donwolf.com

H₂S
CO
O₂
SO₂
NH₃
PH₃
Cl₂
ClO₂
NO
NO₂
HCN
ETO
O₃

**WATER
RESISTANT**



Easy gas identification with color coded labels:



- Direct, real-time readings on large LCD
- Operates through consecutive shifts—exceptional battery run-time
- Secure and accurate history with datalogging




BW
Technologies
by Honeywell

Wear yellow. Work safe.

Standard features of BW products:

- Continuous LCD shows real-time gas concentrations
- Compact and lightweight design makes it comfortable to wear
- Water-resistant
- Simple automatic calibration procedure; compatible with BW MicroDock II automatic test and calibration station
- Full function self-test of sensor, battery status, circuit integrity and audible/visual alarms on start up
- Bright wide-angled visual alarm bars
- Built-in concussion-proof boot

GasAlert Extreme Specifications

Size	1.1 x 2.0 x 3.75 in. / 2.8 x 5.0 x 9.5 cm	
Weight	2.9 oz. / 82 g	
Alarms	- Visual, vibrating, audible (95dB) - Low, High, STEL, TWA	
Tests	Sensor integrity, circuitry, battery and audible/visual alarms on activation, battery (continuous)	
Pump	Compatible with the Sampler motorized pump	
Typical battery life	2 year battery life (typical) with replaceable 3V battery	
User options	Confidence beep	Automatic backlight
	Latching alarms	User-settable calibration gas level
	Stealth mode	
	Passcode protection	Calibration past due lockout
	Automatic O ₂ Calibration	Language choices (5)
	Datalogger Sampling Rate	Adjust clock
Ratings	EMI/RFI: Complies with EMC Directive 89/336/EEC IP 66/67	
Certifications and approvals	 Class I, Div. 1, Gr. A, B, C, D Class II, Div. 1, Gr. E, F, G  American Bureau of Shipping ATEX: CE  II 1 G T4 Ex ia IIC T4 IECEx: Ex ia IIC T4 CE: European Conformity	
Warranty	Full 2 year warranty including sensors (1 year NH ₃ sensor)	

Additional GasAlert Extreme features:

- Equipped with internal vibrating alarm for high noise areas
- Secure and accurate history with datalogging
- Multi-language support in English, French, German, Spanish and Portuguese
- Tamper-proof settings with passcode protection

Options and Accessories



MicroDock II compatible



Concussion-proof boot



SamplerPak Motorized Pump



IR DataLink

For a complete list of accessories, please contact BW Technologies.

Sensor Specifications

Gas	Measuring Range (ppm)	Operating Temperature	Relative Humidity (non-condensing)
H₂S	0-100	-40 to +122°F/-40 to +50°C	15% - 90%
H₂S (High Range)	0-500	-40 to +122°F/-40 to +50°C	15% - 90%
SO₂	0-100.0	-40 to +122°F/-40 to +50°C	15% - 90%
HCN	0-30.0	-40 to +122°F/-40 to +50°C	15% - 90%
CO	0-1000	-22 to +122°F/-30 to +50°C	15% - 90%
CO (Low H₂)	0-1000	-22 to +122°F/-30 to +50°C	15% - 90%
NH₃	0-100	-4 to +104°F/-20 to +40°C	15% - 90%
NH₃ (High Range)	0-400	-4 to +104°F/-20 to +40°C	15% - 90%
Cl₂	0-50.0	-4 to +122°F/-20 to +50°C	10% - 95%
NO	0-250	-4 to +122°F/-20 to +50°C	15% - 90%
NO₂	0-100	-4 to +122°F/-20 to +50°C	15% - 90%
PH₃	0-5.0	-4 to +122°F/-20 to +50°C	15% - 90%
ETO	0-100.0	-4 to +122°F/-20 to +50°C	15% - 90%
ClO₂	0-1.0	-4 to +122°F/-20 to +50°C	15% - 95%
O₃	0-1.0	-4 to +122°F/-20 to +50°C	15% - 90%
O₂ (%by Vol.)	0-30.0%	-4 to +122°F/-20 to +50°C	0% - 99%

Alarm set points for all sensors are user adjustable. Set point(s) are automatically displayed during instrument start up.

Locally available from

Don Wolf & Associates, Inc

21955 Plummer Street

Chatsworth, CA 91311

Toll Free: (800) 266-2046

Phone: (818) 885-5800

Fax: (818) 885-5855

Website: www.donwolf.com

Email: sales@donwolf.com



Corporate Headquarters

2840 - 2 Avenue S.E.
Calgary, AB, Canada T2A 7X9
Phone: +1-403-248-9226

USA 1.888.749.8878
Canada 1.800.663.4164
Australia +61.3.9464.2770

Europe +44 (0)1295 700 300
France +33 (0) 442 98 17 70
Middle East +971-4-8871766

China +86 10 6786 7305
S.E. Asia +65 6580 3468
Other Countries +1-403-248-9226

www.gasmonitors.com

info@gasmonitors.com

DUE TO ONGOING RESEARCH AND PRODUCT IMPROVEMENT, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.